



255 Wooster Road North • Barberton, Ohio 44203  
Phone: (330) 745-9016 • Fax: (330) 745-4886  
www.tahomarubberplastics.com

## DIAMOND EMBOSSED POLYETHYLENE FILM (Elastomer Separator Sheet)

### Features:

- Buy American - Manufactured in our two USA Plants
- Produced from **Prime** PE Resins
- Formulated to achieve maximum tear resistance
- Multiple embossed surfaces available

### Benefits:

- Clear or Standard Tints (Color) at the **same** price
- Custom Colors upon request
- High Release additive agent included where applicable
- Stocking Programs at two North American Sites
- Standard widths up to 64 inch
- Custom widths upon request
- Put up on 13" outside diameter rolls, alternate on request

### Thickness

### Maximum Emboss (A)

### Typical Length 13" (O.D.)

|       |                |                       |
|-------|----------------|-----------------------|
| 3 mil | 11 mil (10-11) | 1500 feet (1400-1600) |
| 4 mil | 14 mil (12-14) | 1300 feet (1300-1400) |
| 5 mil | 16 mil (14-16) | 1100 feet (1000-1200) |
| 6 mil | 18 mil (16-18) | 900 feet (900-1000)   |

*8-10 mil available upon request*

### Packaging:

- Rolls on heavy duty 3 inch (I.D.) cores
- Nine rolls cradled on a pallet – less than nine upon request
- Narrow widths may exceed nine rolls per pallet

### Chemistry

- Polymer: LDPE/LLDPE Blend
- Density: .92 ± .02 grams/cc
- Melt Point: 115C ± 10 Deg C
- Melt Index: 1 –2 Grams/10 Minute Flow

The data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risks of use, storage and handling of product. **No warranty, express or implied, is made including, but not limited to, implied warranties of merchantability and fitness for a particular purpose.** Nothing contained herein shall be construed as a license to operate under, or recommended to infringe, any patents.